



Geräte-Typ	Arbeitshöhe (AH)	Plattformhöhe (PH)	Geräte-Breite GB	Geräte-Länge GL	Geräte-Höhe GH	Plattformbreite PB	Plattformlänge PL	Plattform-Verlängerung PFL	Transport-Höhe TH	Tragkraft der Plattform
SSBG 6	8,10 m	6,10 m	1,60 m	3,00 m	2,57 m	1,60 m	3,00 m	1,00 m	2,57 m	350 kg
SSBG 8	10,10 m	8,10 m	1,60 m	3,00 m	2,57 m	1,60 m	3,00 m	1,00 m	2,57 m	350 kg
SSBG 10	12,10 m	10,10 m	1,60 m	3,00 m	2,57 m	1,60 m	3,00 m	1,00 m	2,57 m	350 kg
SSBG 11	13,10 m	11,10 m	1,60 m	3,00 m	2,57 m	1,60 m	3,00 m	1,00 m	2,57 m	350 kg
SSBD 8	9,80 m	7,90 m	1,72 m	2,70 m	2,32 m	1,54 m	2,51 m	1,52 m	2,32 m	567 kg
SSBD 8 W	9,92 m	7,92 m	1,72 m	3,35 m	2,39 m	1,42 m	2,44 m	1,52 m	1,61 m	567 kg
SSBD 10/1 W	12,15 m	10,15 m	1,80 m	2,65 m	2,54 m	1,54 m	2,50 m	1,20 m	2,54 m	450 kg
SSBD 10 W	11,75 m	9,75 m	1,72 m	3,35 m	2,46 m	1,42 m	2,44 m	1,52 m	1,75 m	454 kg
SSBD 12	14,30 m	12,19 m	2,29 m	4,70 m	3,03 m	1,80 m	3,20 m	1,23 m	2,49 m	455 kg
SSBD 15	17,30 m	15,30 m	2,29 m	4,70 m	3,13 m	1,80 m	4,27 m	2 x 1,23 m	2,45 m	907 kg
SSBD 16	18,00 m	16,00 m	2,25 m	5,30 m	2,97 m	1,89 m	5,30	2 x 1,00 m	2,11 m	500 kg
SSBD 20/1	22,30 m	20,30 m	2,40 m	4,80m	3,76 m	2,30 m	4,35 m	2,85 m	2,96 m	750 kg
SSBD 20/2	22,50 m	20,50 m	2,55 m	5,74 m	3,89 m	2,50 m	5,37 m	2,20 m	3,00 m	1000 kg
SSBD 24	26,50 m	24,50 m	2,51 m	5,77 m	4,20 m	2,51 m	5,35 m	2,20 m	3,10 m	750 kg
SSBD 26	28,00 m	26,00 m	2,50 m	6,88 m	4,20 m	2,50 m	6,70m	3,10 m	3,10 m	1000 kg
SSBD 32	34,00 m	32,00 m	3,00 m	8,40 m	4,65 m	2,80 m	7,85m	3,15 m	3,63 m	1000 kg

ALLRAD-SCHEREN-HUB-ARBEITS-BÜHNEN

Leergewicht	Antrieb	Tankgröße	Bodenfreiheit	Steigfähigkeit	Allrad	Lenkung (Anzahl Räder)	Stützen	Pendelachse	Weißer Räder	Ausgeschäumt	Differential
2971 kg	Batterie	230 V	0,17 m	30%	■	2	□	■	□	■	■
2971 kg	Batterie	230 V	0,17 m	30%	■	2	□	■	□	■	■
2971 kg	Batterie	230 V	0,17 m	30%	■	2	□	■	□	■	■
2971 kg	Batterie	230 V	0,17 m	30%	■	2	□	■	□	■	■
2971 kg	Diesel	54,90 l	0,20 m	40%	■	2	□	□	□	■	□
3305 kg	Diesel	80,00 l	0,20 m	50%	■	2	■	■	■	■	■
3830 kg	Diesel	30,00 l	0,25 m	40%	■	2	■	□	■	■	■
3655 kg	Diesel	80,00 l	0,20 m	40%	■	2	■	■	■	■	■
4900 kg	Diesel	56,80 l	0,31 m	45%	■	4	■	■	□	■	□
6940 kg	Diesel	56,80 l	0,31 m	45%	■	4	■	■	□	■	□
7490 kg	Diesel	65,00 l	0,35 m	45%	■	2	■	□	□	■	■
11 400 kg	Diesel	60,00 l	0,24 m	25%	■	2	■	■	□	■	□
14 800 kg	Diesel	60,00 l	0,30 m	30%	■	2	■	■	□	■	□
16 300 kg	Diesel	60,00 l	0,18 m	30%	■	2	■	■	□	■	□
24 700 kg	Diesel	60,00 l	0,18 m	30%	■	2	■	■	□	■	□
39 800 kg	Diesel	60,00 l	0,45 m	20%	■	2	■	■	□	■	□

